

Digital external measuring instruments

Digital external measuring instruments for measurements of external grooves, axis diameters, wall thicknesses and other hard-to-reach places.

- Measuring range: 0-60 mm.
- Resolution: 0.005 mm. Digital-analog display changes automatically between 0.01, 0.02 and 0.05 mm (± 20 scale divisions).
- mm/inch conversion.
- ABS/INC switchable.
- Large LCD display, 340° rotatable.
- On/off switch.
- Automatic switch-off.
- Reset/preset.
- Hold and min/max functions.
- Adjustable tolerance limits.
- Measuring faces with different contact forms.
- Power supply: 1 battery type CR2032.



908.850

Item No.	Measuring range/mm	Accuracy mm	Length/mm			Contact form/mm
L A B						
Travel 10 mm:						
908.850	0-10	±0.02	40	3	8	① R 0.5
908.851	10-20	±0.02	40	3	8	① R 0.5
908.852	20-30	±0.02	40	3	8	① R 0.5
908.853	30-40	±0.02	40	3	8	① R 0.5
908.854	40-50	±0.02	40	3	8	① R 0.5
908.855	0-10	±0.02	40	3	8	② ø1.5
908.856	10-20	±0.02	40	3	8	② ø1.5
908.857	20-30	±0.02	40	3	8	② ø1.5
908.858	30-40	±0.02	40	3	8	② ø1.5
908.859	40-50	±0.02	40	3	8	② ø1.5
Travel 20 mm:						
908.860	0-20	±0.03	80	6.5	25	① R 0.75
908.861	10-30	±0.03	80	6.5	25	① R 0.75
908.862	20-40	±0.03	80	6.5	25	① R 0.75
908.863	30-50	±0.03	80	6.5	25	① R 0.75
908.864	40-60	±0.03	80	6.5	25	① R 0.75
908.865	0-20	±0.03	80	6.5	25	② ø1.5
908.866	10-30	±0.03	80	6.5	25	② ø1.5
908.867	20-40	±0.03	80	6.5	25	② ø1.5
908.868	30-50	±0.03	80	6.5	25	② ø1.5
908.869	40-60	±0.03	80	6.5	25	② ø1.5
Option:						
495.157	Spare battery					

