

GD-CT-AC2116T

2 MP Bullet HD-TVI Camera 3.6mm IR LED



- 2 Megapixel HD-TVI Camera with HD 1080P real time video
- Smart IR Control
- Lens: $f = 3.6 \text{ mm}$
- 0 Lux: Integrated LED IR Illuminator viewable distance up to 20m
- Power Input DC12V
- 3 Axis Gimbal for wall and ceiling mount



ESSENTIAL

- Product Line Essential: high quality, basic features and remarkably many functions for smaller applications

Item Code: GD-CT-AC2116T

EAN CODE: 4260573060467

® Abetechs GmbH (Grundig Security), Düsseldorf, Germany

grundig-security.com

Specifications GD-CT-AC2116T

Camera

Image Sensor:	2 Megapixel progressive scan CMOS
Pixels - Effective:	1920 (H) x 1080 (V)
Sensitivity Colour:	0.01 Lux @ F1.2 (AGC ON)
Sensitivity B/W:	0 Lux LED IR on
Shutter Speed:	1/25 (1/30) ~ 1/50,000 s
White Balance:	Auto , Manual

Lens

Lens Focal Length:	3.6 mm
Horizontal Viewing Angle:	82.2°
F-Stop:	F2.0
Lens Mount:	M12

Illuminator

Max. IR Distance:	Up to 20 m
Wavelength:	850nm

Video

Video Standard:	PAL, NTSC
Col/B&W:	Auto , Color , B&W, IR-cut filter removable (ICR)
Wide Dynamic Range:	Digital WDR
Image Enhancement:	BLC, 2D DNR, Anti-Flicker, Mirror, AGC
S/N Ratio:	>62 dB
Frame Rate (Max@Resolution):	PAL: 1080p@25fps NTSC: 1080p@30fps

General

OSD (On Screen Display):	English
Coaxial control:	Control over Coax (CoC)

I/O Interface

Video Outputs:	1x HD-TVI (BNC)
----------------	-----------------

Approvals

Regulation:	CE, EAC, FCC, RoHS Compliant
Protection Rating:	IP66

Environmental

Operating Temperature:	-40 °C ~ 60 °C (-40 °F ~ 140 °F)
Humidity:	less than 95%, non condensing

Electrical

Supply Voltage:	12 VDC ±10%
Power Consumption:	Max. 4 W

Item Code: GD-CT-AC2116T

EAN CODE: 4260573060467

Mechanical

Mount:	Pan: 0° to 360°, tilt: 0° to 90°, rotation: 0° to 360°, 3-Axis Adjustment
Dimensions:	150 x 55 x 58 mm (5.9 x 2.17 x 2.28 inch)
Weight:	300 g (0.64 lb)

Accessories:



GD-BR-AJX05



GD-AC-VB01