

GD-CT-AC2113E

2 MP Eyeball HD-TVI Camera 2.8mm IR LED



- 2 Megapixel HD-TVI Camera with HD 1080P real time video
- Smart IR Control
- Lens: $f = 2.8 \text{ mm}$
- 0 Lux: Integrated LED IR Illuminator viewable distance up to 20m
- 3 Axis Gimbal for wall and ceiling mount
- Power Input DC12V



ESSENTIAL

- Product Line Essential: high quality, basic features and remarkably many functions for smaller applications

Item Code: GD-CT-AC2113E

EAN CODE: 4260573060412

® Abetechs GmbH (Grundig Security), Düsseldorf, Germany

grundig-security.com

Specifications GD-CT-AC2113E

Camera

Image Sensor:	2 Megapixel progressive scan CMOS
Pixels - Effective:	1984 (H) x 1105 (V)
Sensitivity Colour:	0.01 Lux @ F1.2 (AGC ON)
Sensitivity B/W:	0 Lux LED IR on
Shutter Speed:	1/25 (1/30) ~ 1/50,000 s
White Balance:	ATW, Manual

Lens

Lens Focal Length:	2.8 mm
Horizontal Viewing Angle:	106°
F-Stop:	F2.0
Lens Mount:	M12

Illuminator

Max. IR Distance:	Up to 20 m
Wavelength:	850nm

Video

Video Standard:	PAL, NTSC
Col/B&W:	Auto , Color , B&W, IR-cut filter removable (ICR)
Wide Dynamic Range:	Digital WDR
Image Enhancement:	BLC, 2D DNR, Anti-Flicker, Mirror, AGC
S/N Ratio:	>62 dB
Frame Rate (Max@Resolution):	PAL: 1080p@25fps NTSC: 1080p@30fps

General

OSD (On Screen Display):	English
Coaxial control:	Coaxitron®, CCVC

I/O Interface

Video Outputs:	1x HD-TVI (BNC)
----------------	-----------------

Approvals

Regulation:	CE, EAC, FCC, RoHS Compliant
Protection Rating:	IP66

Environmental

Operating Temperature:	-40 °C ~ 60 °C (-40 °F ~ 140 °F)
Humidity:	less than 95%, non condensing

Electrical

Supply Voltage:	12 VDC ±10%
Power Consumption:	Max. 4 W

Item Code: GD-CT-AC2113E

EAN CODE: 4260573060412

Mechanical

Mount:	Pan: 0° to 360°, tilt: -90° to 90°, rotation: 0° to 360°, 3-Axis Adjustment
Dimensions:	Ø 89.6 x 59.1 mm (3.53 x 2.33 inch)
Weight:	400 g (0.88 lb)

Accessories:



GD-BR-AMW14



GD-BR-AJX05



GD-AC-VB01