




OKS 1351 - Product Information

Fields of Application:

Release agent for the processing of plastics and elastomers. Against sticking of glues and sealing materials. Sliding film for plastics, elastomers and metals with each other. For easy permeation of plastic and elastomere profiles. For the lubrication of cutting edges in paper, cardboard, veneer and textile machines.

OKS 1351 Silicone Spray



Advantages and Benefits:

High efficiency by distinctive surface wetting. Manifold application for a long time lubrication, protection, maintenance and impregnation. Formation of extrem thin films. Waterresistant and weatherproof.

Application:

For optimal effect clean surface, first mechanically and then with OKS 2610/OKS 2611 Universal Cleaner. Spray on evenly thin from about 20 - 30 cm distance. Avoid excess. Only mix with appropriate lubricants. Plastics based on silicone could be effected by silicone oil. At sliding aereas with pure oxigen no silicone has to be used. For further questions please contact our Technical Department.

Additional Information:

Packaging (article number):
- 600 ml Spray (01351006)

Version:
E-01.1/08

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



OKS 1351 Silicone Spray

Technical Data

	Norm	Conditions	Unit	Value
Base Oil				
Type				Polydimethylsiloxane
Viscosity	DIN 51 562-1	+25°C	mm ² /s	350
Pour point	DIN ISO 3016	3°C step	°C	-50
Flash point	DIN ISO 2592	> 79	°C	> 300
Application Data				
Density	DIN EN ISO 3838	+20°C	g/ml	0,97
Colour				light coloured
Service Temperatures				
Minimum service temperature			°C	-50
Maximum service temperature			°C	200

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark