



● UT136C+

- Measures up to 1000V and 10A AC/DC voltage and current
- Equipped with 3mm protective sleeve; 2 meters drop proof
- Large LCD display; Overload alarm
- Quick sampling rate, up to 4 times/s
- Quick capacitor measurement (measures 1mF in 4 seconds)
- Low power consumption and auto power saving function; long battery service life (>500hrs)

SPECIFICATIONS

	Range	UT136B+	UT136C+
DC voltage (V)	1000V	±(0.7%+3)	±(0.7%+3)
AC voltage (V)	1000V	±(1%+3)	±(1%+3)
DC current (A)	10A	±(1%+3)	±(1%+3)
AC current (A)	10A	±(1.2%+5)	±(1.2%+5)
Resistance (Ω)	40MΩ	±(0.8%+2)	±(0.8%+2)
Capacitance (F)	40mF	±(3%+5)	±(3%+5)
Frequency (Hz)	400Hz~40mHz	±(0.1%+4)	±(0.1%+4)
Temperature (°C)	-40~1000°C		±(1%+4)
Temperature (°F)	-40~1832°F		±(1.5%+5)

Features

Display count		4000	4000
hFE	Transistor measurement	√	√
NCV	Non-contact voltage detection	√	
Diode/transistor		√	√
Continuity buzzer		√	√
Data hold/Auto power off		√	√
Low battery/Indication		√	√
LCD backlight		√	√
Safety rating	CAT II 1000V, CAT III 600V	√	√
Drop test	2m	√	√



GENERAL CHARACTERISTICS

Power	1.5V battery (R6) x 2
Display	56.5mm x 36mm
Product color	Red and grey
Product net weight	330g
Product size	175mm x 83mm x 53mm
Standard accessories	Batteries, test leads, temperature probe (UT136C+)
Standard individual packing	Gift Box, English manual
Standard quantity per carton	30pcs
Standard carton measurement	390mm x 335mm x 340mm
Standard carton gross weight	12.75kg