

HF871

	Material Group ISO 513	P1 P2 M1 K1			P3 P4 M2 K2 K3			P5 M3 M4 K4 S1 S4			S2 S3 S5		
	Hardness/Rm	≤ 700 N/mm ²			700-1000 N/mm ²			≤ 35 HRC			≤ 40 HRC		
	ap x ae	D x D			D x D			0.5D x D			0.5D x D		
	Vc (m/min)	130-150			80-100			60-80			30-50		
	D (mm)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)
	1	30000	0.005	600	28660	0.005	520	22290	0.004	330	12740	0.004	180
	1.5	29720	0.008	890	19110	0.007	520	14860	0.006	330	8490	0.005	180
	2	22290	0.010	890	14330	0.009	520	11150	0.008	330	6370	0.007	180
	3	14860	0.014	830	9550	0.013	480	7430	0.011	310	4250	0.010	170
	4	11150	0.019	830	7170	0.017	480	5570	0.014	310	3180	0.013	160
	5	8920	0.023	820	5730	0.021	470	4460	0.017	310	2550	0.016	160
	6	7430	0.027	800	4780	0.024	460	3720	0.020	300	2120	0.019	160
	8	5570	0.035	780	3580	0.032	450	2790	0.026	290	1590	0.025	160
	10	4460	0.042	750	2870	0.038	430	2230	0.032	280	1270	0.029	150
	12	3720	0.048	710	2390	0.043	410	1860	0.036	270	1060	0.034	140
	14	3180	0.054	690	2050	0.049	400	1590	0.041	260	910	0.038	140
	16	2790	0.060	670	1790	0.054	390	1390	0.045	250	800	0.042	130
	18	2480	0.066	650	1590	0.059	380	1240	0.050	250	710	0.046	130
	20	2230	0.073	650	1430	0.066	380	1110	0.055	240	640	0.051	130
ap x ae	D1	0.25D x D											
ap x ae	≤ D3	0.5D x D											

	Material Group ISO 513	P1 P2 M1 K1			P3 P4 M2 K2 K3								
	Hardness/Rm	≤ 700 N/mm ²			700-1000 N/mm ²								
	ap x ae	1.5D x D			1.5D x D								
	Vc (m/min)	100-120			60-80								
	D (mm)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)						
	8	4380	0.028	490	2790	0.025	280						
	10	3500	0.034	470	2230	0.030	270						
	12	2920	0.038	450	1860	0.035	260						
	14	2500	0.043	430	1590	0.039	250						
	16	2190	0.048	420	1390	0.043	240						
	18	1950	0.053	410	1240	0.048	240						
	20	1750	0.058	410	1110	0.053	230						

	Material Group ISO 513	P1 P2 M1 K1											
	Hardness/Rm	≤ 700 N/mm ²											
	ap x ae	2D x D											
	Vc (m/min)	75-95											
	D (mm)	n (rpm)	fz (mm/z)	Vf (mm/min)									
	10	2710	0.025	270									
	12	2260	0.029	260									
	14	1930	0.032	250									
	16	1690	0.036	240									
	18	1500	0.040	240									
	20	1350	0.044	240									

PARAMETERS SUGGESTED WITH HIGH PRECISION WELDON CHUCK AND STABLE MACHINING CONDITION.
FOR APPLICATION ON HIGH POWER MILLING CHUCK, PLEASE REFER TO HF840 PARAMETERS.

HF871

	Material Group ISO 513	P1 P2 M1 K1			P3 P4 M2 K2 K3			P5 M3 M4 K4 S1 S4			S2 S3 S5		
	Hardness/Rm	≤ 700 N/mm ²			700-1000 N/mm ²			≤ 35 HRC			≤ 40 HRC		
	ap x ae	1.5D x 0.5D			1.5D x 0.5D			1.2D x 0.3D			1.2D x 0.3D		
	Vc (m/min)	160-180			100-120			70-90			40-60		
	D (mm)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)
	1	30000	0.006	720	30000	0.005	650	25480	0.005	490	15920	0.007	420
	1.5	36090	0.009	1300	23350	0.008	760	16990	0.007	490	10620	0.010	420
	2	27070	0.012	1300	17520	0.011	760	12740	0.010	490	7960	0.013	420
	3	18050	0.017	1210	11680	0.015	710	8490	0.013	460	5310	0.018	390
	4	13540	0.022	1200	8760	0.020	700	6370	0.018	450	3980	0.024	390
	5	10830	0.028	1200	7010	0.025	700	5100	0.022	450	3180	0.030	390
	6	9020	0.032	1170	5840	0.029	680	4250	0.026	440	2650	0.036	380
	8	6770	0.042	1140	4380	0.038	660	3180	0.034	430	1990	0.046	370
	10	5410	0.050	1090	3500	0.045	640	2550	0.040	410	1590	0.055	350
	12	4510	0.058	1040	2920	0.052	610	2120	0.046	390	1330	0.063	340
	14	3870	0.065	1000	2500	0.058	580	1820	0.052	380	1140	0.071	330
	16	3380	0.072	970	2190	0.065	570	1590	0.058	370	1000	0.079	320
	18	3010	0.079	950	1950	0.071	560	1420	0.063	360	880	0.087	310
	20	2710	0.088	950	1750	0.079	550	1270	0.070	360	800	0.096	310
ap x ae	≤ D3	1.5D x 0.1D											

	Material Group ISO 513	P1 P2 M1 K1			P3 P4 M2 K2 K3			P5 M3 M4 K4 S1 S4			S2 S3 S5		
	Hardness/Rm	≤ 700 N/mm ²			700-1000 N/mm ²			≤ 35 HRC			≤ 40 HRC		
	α° x ae	5° x 0.4D			4° x 0.4D			3° x 0.4D			3° x 0.4D		
	Vc (m/min)	130-150			80-100			60-80			30-50		
	D (mm)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)
	1	30000	0.004	435	28660	0.003	390	22290	0.003	268	12740	0.003	143
	1.5	29720	0.005	650	19110	0.005	390	14860	0.005	268	8490	0.004	143
	2	22290	0.007	650	14330	0.007	390	11150	0.006	268	6370	0.006	143
	3	14860	0.010	605	9550	0.010	365	7430	0.008	250	4250	0.008	133
	4	11150	0.013	600	7170	0.013	360	5570	0.011	247	3180	0.010	132
	5	8920	0.017	600	5730	0.016	360	4460	0.014	246	2550	0.013	131
	6	7430	0.020	585	4780	0.018	350	3720	0.016	241	2120	0.015	128
	8	5570	0.025	570	3580	0.024	340	2790	0.021	235	1590	0.020	125
	10	4460	0.031	545	2870	0.029	325	2230	0.025	225	1270	0.024	120
	12	3720	0.035	520	2390	0.033	310	1860	0.029	214	1060	0.027	114
	14	3180	0.039	500	2050	0.037	300	1590	0.032	206	910	0.030	110
	16	2790	0.044	490	1790	0.041	290	1390	0.036	200	800	0.034	108
	18	2480	0.048	475	1590	0.045	285	1240	0.040	197	710	0.037	105
	20	2230	0.053	475	1430	0.050	285	1110	0.044	195	640	0.041	105
α° max	≤ D3	1°											

PARAMETERS SUGGESTED WITH HIGH PRECISION WELDON CHUCK AND STABLE MACHINING CONDITION.
FOR APPLICATION ON HIGH POWER MILLING CHUCK, PLEASE REFER TO HF840 PARAMETERS.

HF871

	Material Group ISO 513	P1 P2 M1 K1				P3 P4 M2 K2 K3				P5 M3 M4 K4 S1 S4				S2 S3 S5		
	Hardness/Rm	≤ 700 N/mm ²				700-1000 N/mm ²				≤ 35 HRC				≤ 40 HRC		
	α° x ae	15° x D				10° x D				5° x D				5° x D		
	Vc (m/min)	130-150				80-100				60-80				30-50		
	D (mm)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)
	6	7430	0.022	640	4780	0.020	380	3720	0.019	281	2120	0.026	220			
	8	5570	0.028	620	3580	0.026	370	2790	0.024	273	1590	0.034	214			
	10	4460	0.034	600	2870	0.031	355	2230	0.029	262	1270	0.040	205			
	12	3720	0.038	570	2390	0.035	335	1860	0.034	250	1060	0.046	196			
	14	3180	0.043	550	2050	0.040	325	1590	0.038	240	910	0.052	189			

	Material Group ISO 513	P1 P2 M1 K1				P3 P4 M2 K2 K3				P5 M3 M4 K4 S1 S4				S2 S3 S5		
	Hardness/Rm	≤ 700 N/mm ²				700-1000 N/mm ²				≤ 35 HRC				≤ 40 HRC		
	ap x ae	D x 0.4D				D x 0.4D				D x 0.25D				D x 0.25D		
	Vc (m/min)	130-150				80-100				60-80				30-50		
	D (mm)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)
	6	7430	0.027	800	4780	0.024	460	3720	0.020	300	2120	0.019	160			
	8	5570	0.035	780	3580	0.032	450	2790	0.026	290	1590	0.025	160			
	10	4460	0.042	750	2870	0.038	430	2230	0.032	280	1270	0.029	150			
	12	3720	0.048	710	2390	0.043	410	1860	0.036	270	1060	0.034	140			
	14	3180	0.054	690	2050	0.049	400	1590	0.041	260	910	0.038	140			

	Material Group ISO 513	P1 P2 M1 K1				P3 P4 M2 K2 K3				P5 M3 M4 K4 S1 S4				S2 S3 S5		
	Hardness/Rm	≤ 700 N/mm ²				700-1000 N/mm ²				≤ 35 HRC				≤ 40 HRC		
	ap x ae	D x D				D x D				0.5D x D				0.5D x D		
	Vc (m/min)	100-120				60-80				45-65				20-40		
	D (mm)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)
	1	30000	0.003	300	22290	0.002	200	17520	0.002	140	9550	0.003	110			
	1.5	23350	0.004	350	14860	0.003	200	11680	0.003	140	6370	0.004	110			
	2	17520	0.005	350	11150	0.005	200	8760	0.004	140	4780	0.006	110			
	3	11680	0.007	330	7430	0.006	190	5840	0.006	130	3180	0.008	100			
	4	8760	0.009	320	5570	0.008	190	4380	0.007	130	2390	0.010	100			

PARAMETERS SUGGESTED WITH HIGH PRECISION WELDON CHUCK AND STABLE MACHINING CONDITION.
FOR APPLICATION ON HIGH POWER MILLING CHUCK, PLEASE REFER TO HF840 PARAMETERS.

HF871

	Material Group ISO 513	P1	P2	M1	K1	P3	P4	M2	K2	K3	P5	M3	M4	K4	S1	S4	S2	S3	S5
	Hardness/Rm	≤ 700 N/mm ²				700-1000 N/mm ²				≤ 35 HRC				≤ 40 HRC					
	ap x ae	2D x 0.2D				2D x 0.1D				1.5D x 0.1D				1.5D x 0.1D					
	Vc (m/min)	190-230				130-150				100-120				50-70					
	D (mm)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)	n (rpm)	fz (mm/z)	Vf (mm/min)						
	1	30000	0.013	1500	30000	0.011	1350	30000	0.010	1200	19110	0.014	1050						
	1.5	23350	0.019	1750	29720	0.017	2010	23350	0.015	1400	12740	0.021	1050						
	2	30000	0.025	3000	22290	0.023	2010	17520	0.020	1400	9550	0.028	1050						
	3	22290	0.035	3120	14860	0.032	1870	11680	0.028	1310	6370	0.039	980						
	4	16720	0.046	3090	11150	0.042	1860	8760	0.037	1300	4780	0.051	970						
	5	13380	0.058	3080	8920	0.052	1850	7010	0.046	1290	3820	0.063	970						
	6	11150	0.068	3010	7430	0.061	1810	5840	0.054	1260	3180	0.074	940						
	8	8360	0.088	2930	5570	0.079	1750	4380	0.070	1230	2390	0.096	920						
	10	6690	0.105	2810	4460	0.095	1690	3500	0.084	1180	1910	0.116	880						
	12	5570	0.120	2670	3720	0.108	1610	2920	0.096	1120	1590	0.132	840						
14	4780	0.135	2580	3180	0.122	1550	2500	0.108	1080	1360	0.149	810							
16	4180	0.150	2510	2790	0.135	1510	2190	0.120	1050	1190	0.165	790							
18	3720	0.165	2460	2480	0.149	1470	1950	0.132	1030	1060	0.182	770							
20	3340	0.183	2440	2230	0.164	1470	1750	0.146	1020	960	0.201	770							
ap x ae	D1	D x 0.1D			D x 0.1D			D x 0.1D			D x 0.1D								
ap x ae	≤ D3	1.5D x 0.1D			1.5D x 0.1D			D x 0.1D			D x 0.1D								

NOTES:

Down milling CNC programming is required.

"ae" value max 0.2xD - "T" value max 0.1xD.

The use of end mill with diameter 30-40% smaller than the width of the slot is recommended.

The cutting conditions are based on CNC programming with medium dynamic speed.

With lower CNC dynamic speed, use the same cutting conditions or reduce the cutting speed Vc.

With higher CNC dynamic speed, reduce the "T" value by approximately -30 -50% and apply the maximum available cutting speed Vc.

