

Hour meters - TBW series

- ▶ Front panel mounting
- ▶ Mounting aperture 50 x 25mm
- ▶ Without zero reset



▶ Technical data

▶ 1. Indicators

Counter capacity:	99 999h
Accuracy of reading:	0.01h
Numeral colour:	white, decimal figures red
Numeral height:	4.4mm
Operation indicator:	fast-running wheel

▶ 2. Mechanical design

Self-extinguishing plastic housing, IP rating IP54 (on the front)	
Class of protection II	
Front panel mounting	
Shockproof terminal connection according to VBG 4 (terminals IP rating IP00 / AMP plug-type connections 6.3 x 0.8mm)	
Initial torque:	max. 2.4Nm
Terminal capacity:	cylinder head bolt M3x5, DIN 84

▶ 3. Input circuit

Supply voltage:	230V AC
Tolerance:	±10%
Rated frequency:	50Hz
Rated consumption:	approx. 1.5VA

▶ 4. Ambient conditions

Ambient temperature:	-15 to +50°C
Storage temperature:	-15 to +50°C
Transport temperature:	-15 to +50°C
Relative humidity:	<90%

▶ 5. Accessories

SB-TBX30:	Retaining clip for fixing the device in front panel aperture
-----------	--

Dimensions

