

	Product Information LPP80-35-15/2	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	
		Date	
Project Name		Client Name	LEO Sibir LLC
		Client Addr.	Novosibirsk
Item NO		Contacts	
		Contact	


Part NO.	LPP80-35-15/2		
Product Picture		Note	
		: CFD	
Nameplate parameters			
flow	110 m³/h		
head	35 m		
speed	2950 rpm		
number of stages	1		
Technical			
Curve tolerance	ISO9906 AnnexA		
Maximum lift (m)	42		
Minimum usage flow (m³/ h)	11		
Maximum use flow (m³/ h)	130		
Material			
Impeller	HT200		
Pump inlet	HT200		
Pump shaft	AISI304		
Mechanical seal	SiC/C		
O-ring	NBR		
Working conditions			
Max. ambient temperature (°C)	40		
Max. liquid temperature (°C)	90		
Pumped medium			
Working pressure	16bar		
Installation			
Inlet & Outlet Diameter	DN80		
Connection standard	DIN		
Motor			
Motor phase	Three phase		
Protection class	IP55		
Motor poles	2		
Insulation class	F		
Motor power (KW)	15KW		
Frequency	50		
Rated voltage (V)	380		
Rated current (A)	27.863875241996		
Efficiency class	IE3		
Power factor	0.89		

	Product Information LPP80-35-15/2	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	
		Date	
Project Name		Client Name	LEO Sibir LLC
		Client Addr.	Novosibirsk
Item NO		Contacts	
		Contact	


Drive end bearing	7309
Non-drive end bearing	6208
Efficiency (%)	91.9
Weight/Packaging	
Gross weight (kg)	206
Package size	990*510*640



	Performance Curve LPP80-35-15/2	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	
		Date	
Project Name		Client Name	LEO Sibir LLC
		Client Addr.	Novosibirsk
Item NO		Contacts	
		Contact	




	Pump Technical Parameters LPP80-35-15/2	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	
		Date	
Project Name		Client Name	LEO Sibir LLC
		Client Addr.	Novosibirsk
Item NO		Contacts	
		Contact	

Rated parameters			
Pump model	LPP80-35-15/2		
Part NO.	LPP80-35-15/2		
Rated flow	110 m³/h		
Rated head	35 m		
Rated efficiency (%)	80.5		
Power (kW)	13		
Speed (rpm)	2950		
Max impeller diameter (mm)	180		
Medium			
Pumped medium	Clean Water		
Working temperature (°C)	20		
Medium density (kg/m³)	1000		
Viscosity (mm²/s)	1		



	Installation picture LPP80-35-15/2	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	
		Date	
Project Name		Client Name	LEO Sibir LLC
		Client Addr.	Novosibirsk
Item NO		Contacts	
		Contact	



	Order Data LPP80-35-15/2	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	
		Date	
		Client Name	LEO Sibir LLC
Project Name		Client Addr.	Novosibirsk
Item NO		Contacts	
		Contact	

Pump model LPP80-35-15/2

Part NO. LPP80-35-15/2

Product price

Quantity 1

Total price

Inquiry notes

