

FUEL DISPENSER PUMP HOSE

Construction:

Tube: Nitrile synthetic rubber, smooth

Reinforcement: steel wire braid

Cover: Nitrile synthetic rubber, black, green, red, blue or yellow

Application:

Designed for general refueling equipment to convey aviation kerosene, gasoline, diesel oil and other mineral oil.







Temperature:

-40°C (-104°F) to 121°C (+250°F)

Characteristics:

- Designed for fuel up to 50% aromatic content
- Weather and ozone resistant cover
- C/W coupling SHF



Item Code	 I.D.		 O.D.	 W.P.		 B.P.		 R	 L
	inch	mm	mm	bar	psi	bar	psi	mm	kg/m
FDH016	5/8"	15.9	25.4	18	258	72	1032	160	0.59
FDH019	3/4"	19.1	28.7	18	258	72	1032	190	0.67
FDH025	1"	25.4	35.1	18	258	72	1032	240	0.89

HOT TAR & ASPHALT SUCTION HOSE 150PSI

Construction:

Tube: Black, smooth, special elastomer compound

Reinforcement: 2 or 4 layers high tensile cord with steel wire helix, anti-static wires

Cover: Black, wrapped finish, synthetic elastomer compound for high abrasion, ozone & weather resistance

Application:

Hot tar and asphalt suction hose is specially designed for conveying hot tar and asphalt.






Temperature:

-40°C (-22°F) to 180°C (+356°F)

Characteristics:

- Tube is synthetic oil, abrasion, and heat resistant
- Cover is resistant to weathering and abrasion.
- Special tube is heat resistant up to 180°C
- All sizes are full vacuum



Item Code	 I.D.		 O.D.	 W.P.		 B.P.		 L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
HTSH051	2"	50.8	69	10	150	30	450	61	200
HTSH076	3"	76.2	96	10	150	30	450	61	200
HTSH102	4"	101.6	122	10	150	30	450	61	200