

MTEO 2T R+ Professional 2T Motor Oil

RACING PLUS

LOW SMOKE RACING SERIES *New Improved Formula with Friction Modifier*

Product Description

TOYO MTEO 2T R+ is a Premium Grade Performance and Super Speed 2-strokes motor oil formulated from high quality synthetic ester base stocks and racing additives package.

This product ensure you maximum output of the engine without compromising the reliability and the wear. It is ideal to used in most 2 stroke engines including outboard motors, motorcycles, watercrafts, mopeds, go karts, snow mobiles, scooters and paramotors etc.

TOYO MTEO 2T R+ is specially designed for both injection or premix, leaded or unleaded gasoline application up to a fuel ratio at 50:1. With anti-wear, anti corrosion and anti-foam capabilities.

Product Specification & Performance

JASO FC ISO-L-EGC API TC
JASO FD ISO-L-EGD

Applicable for all kind of two stroke engines

Benefits

- ✓ Preserve Power Output and Enhance Fuel Consumption Efficiency and Economy.
- ✓ Excellent Start-up Protection and Rapid Circulation.
- ✓ Designed to Protect Against High Friction and High Shear.
- ✓ Protection against thermal and machine breakdown.
- ✓ Assist engine cleanliness and virtually smokeless exhaust.
- ✓ Minimizing spark plug fouling to ensure reliable starting.
- ✓ Environment friendly.

50:1

Typical Specifications

	Grade	Test Method	2T R+
	API Gravity	ASTM D-1298	0.860
	Kinematic Viscosity at		
	40°C cSt	ASTM D-445	46
	100°C cSt	ASTM D-445	9.2
	Viscosity Index	ASTM D-2270	187
	Flash Point min °C	ASTM D-93	249
	Pour Point °C	ASTM D-97	-45

This information is our best knowledge, true & accurate, subjected to change without prior notice due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.



MACHINES NEVER LIE

MTEO 2T R+ Professional 2T Motor Oil

RACING PLUS

Other Information

Safety Data Sheet

Safety data sheet can be requested via website www.toyointernational.com or you may also can get them from your local agent / supplier.

SDS Number: LP14-11

Storage and Handling

This product shall be ideally stored in a cool, dry location in unopened containers. Suggested temperature between 8°C to 28°C (46°F to 82°F) unless otherwise labeled.

Stirring is recommended in order to prevent ingredients from separating.

Shelf Life

With good practicing on storage, the minimum shelf life from the batch number approx. 3 years or 36 months

Condition of the product must in the unopened original container

Available Packing Sizes

Bottle 1 liter

Part Number

8696L-0017

Packing Type

12 pcs per box

This information is our best knowledge, true & accurate, subjected to change without prior notice due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

TOYO GREASE
“MACHINES NEVER LIE”