

PRODUCT DATA SHEET

SCOOTER 10W-40 FS 4T

ESTER PERFORMANCE

FULLY SYNTHETIC Special Formulation for all Scooter Engines – Low Emissions

Product description

TOYO-G **SCOOTER 10W-40 FS** is a premium grade, fully-synthetic cum ester engine oil specially developed for all scooter types that are running in automatic transmission (without clutches) and four stroke systems that are trending in low emissions.

It contains with JASO MB performance to ensure engine is being protected for daily commuting and urban ridding. It provides excellent protection against oxidation and corrosion issues. Together with advance friction modifier additives, it provides smoother acceleration in an automatic transmission.

Product Specification & Performance

SAE 10W-40 API SN JASO MB Applicable for all kind of four stroke scooters

Benefits

- ✓ Better Controlling and Smoothest Acceleration Performance
- ✓ Together with advance additives, it helps to reduce unnecessary noise and vibration
- ✓ High Shear stability which offers resistance to viscosity and thermal breakdown during at high temperatures usage
- ✓ Good detergent packages that helps to clean internal parts, remove sludge and deposits formation
- ✓ Contains Anti-wear additives to protect against scuffing and wear

Typical Specifications		
Grade	Test Method	Spec
API Gravity	ASTM D-1298	0.858
Kinematic Viscosity at		
40°C cSt	ASTM D-445	103
100°C cSt	ASTM D-445	15.05
Viscosity Index	ASTM D-2270	153
Flash Point °C	ASTM D-93	222
Pour Point °C	ASTM D-97	-33

This information is our best knowledge, true & accurate, subjected to change without prior notice due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.





PRODUCT DATA SHEET

SCOOTER 10W-40 FS 4T

ESTER PERFORMANCE

Other Information

Safety Data Sheet

Safety data sheet can be requested via website www.toyointernational.com or you may also can get them from your local agent / supplier.

SDS Number: LP14-09

Storage and Handling

This product shall be ideally stored in a cool, dry location in unopened containers. Suggested temperature between 8°C to 28°C (46°F to 82°F) unless otherwise labeled.

Stirring is recommended in order to prevent ingredients from separating.

Shelf Life

With good practicing on storage, the minimum shelf life from the batch number approx. 5 years or 60 months Condition of the product must in the unopened original container

Available Packing Sizes		Part Number	Packing Type	
Bottle	1 liter	8696L-1073	12 pcs per box	
Bottle	4 liter	8696L-0364	4 pcs per box	
Pail	18 liter	8696L-0381		
Drum	209 liter	8696L-0902		

Updated 15.09.2022

This information is our best knowledge, true & accurate, subjected to change without prior notice due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

