




SFU

Гайка шарико-винтовой передачи



Артикул	Размеры, мм									Резьба под маслянку, Q	Динам. нагрузка, С (kN)	Стат. нагрузка, С0 (kN)	Шаг	Дорожек качения	Вес, кг
	d	Dw	D	L	B	A	W	H	X						
SFU1204	12	2,381	22	36	8	42	32	34	4,5	M6	4	6,7	4	3	0,10
SFU1605	16	3,175	28	42	10	48	38	40	5,5	M6	6,3	12,6	5	3	0,15
SFU1610	16	3,175	28	57	10	48	38	40	5,5	M6	7,29	12,5	10	3	0,25
SFU2005	20	3,175	36	51	10	58	47	44	6,6	M6	9,1	17,1	5	3	0,35
SFU2010	20	3,175	36	59	10	58	47	44	6,6	M6	9,7	21,1	10	3	0,30
SFU2505	25	3,175	40	51	12	62	51	48	6,6	M6	10,6	22,1	5	3	0,35
SFU2510	25	3,5	40	85	12	62	51	48	6,6	M6	10,6	27,36	10	4	0,55
SFU3205	32	6,35	50	52	12	80	65	62	9	M6	17,1	42,1	5	4	0,60
SFU3210	32	6,35	50	90	12	80	65	62	9	M6	33,9	71,1	10	4	0,85
SFU4005	40	6,35	63	54	14	93	78	70	9	M6	18,5	57,1	5	4	1,00
SFU4010	40	6,35	63	93	14	93	78	70	9	M6	31,1	95,2	10	4	1,40
SFU5010	50	6,35	75	95	16	110	93	85	11	M6	44,5	12,5	10	4	1,90
SFU6310	63	6,35	90	98	18	125	108	95	11	M6	50,7	16,6	10	4	2,65