



ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ ДЛЯ СТАНДАРТНОПРОХОДНОГО ИСПОЛНЕНИЯ

DN	PN	КОД	D	D1	D2	n отв	h	H	I	L
20	40	KШ.Ц.Ф. Regula 020.040.Н/П.02	105	75	14	4	23	72	159	120
25	40	KШ.Ц.Ф. Regula 025.040.Н/П.02	115	85	14	4	21	75	159	140
32	40	KШ.Ц.Ф. Regula 032.040.Н/П.02	135	100	18	4	21	75	159	140
40	40	KШ.Ц.Ф. Regula 040.040.Н/П.02	145	110	18	4	44	92	217	165
50	40	KШ.Ц.Ф. Regula 050.040.Н/П.02	160	125	18	4	44	100	217	180
65	16	KШ.Ц.Ф. Regula 065.016.Н/П.02	180	145	18	4	44	110	217	200
65	25	KШ.Ц.Ф. Regula 065.025.Н/П.02	180	145	18	8	44	110	217	200
80	16	KШ.Ц.Ф. Regula 080/070.016.Н/П.02	195	160	18	4	60	141	314,5	210
80	25	KШ.Ц.Ф. Regula 080/070.025.Н/П.02	195	160	18	8	60	141	314,5	210
100	16	KШ.Ц.Ф. Regula 100/080.016.Н/П.02	215	180	18	8	60	150	314,5	230
100	25	KШ.Ц.Ф. Regula 100/080.025.Н/П.02	230	190	22	8	60	150	314,5	230
125	16	KШ.Ц.Ф. Regula 125/100.016.Н/П.02	245	210	18	8	94	195	525	350
125	25	KШ.Ц.Ф. Regula 125/100.025.Н/П.02	270	220	26	8	94	195	525	350
150	16	KШ.Ц.Ф. Regula 150/125.016.Н/П.02	280	240	22	8	98	210	525	380
150	25	KШ.Ц.Ф. Regula 150/125.025.Н/П.02	300	250	26	8	98	210	525	380
200	16	KШ.Ц.Ф. Regula 200/150.016.Н/П.02	335	295	22	12	84	225	625	450
200	25	KШ.Ц.Ф. Regula 200/150.025.Н/П.02	360	310	26	12	84	225	625	450
250	16	KШ.Ц.Ф. Regula 250/125.016.Н/П.02	405	355	26	12	100	270	625	530
250	25	KШ.Ц.Ф. Regula 250/125.025.Н/П.02	425	370	30	12	100	270	625	530
300	16	KШ.Ц.Ф. Regula 300/250.025.Н/П.02	460	410	26	12	167	634	-	750