

NOVACORD

SPEAKER 2x1.5 FRNC/LSZH-C



Oxygen Free Copper
99,9%



Flexible
construction





Pure signal
transmission



Audio cables are used in professional broadcasting systems for the transmission of analogue audio signals. Speaker cable features a strand design of 2x1.5 mm² cores pure copper strands. It is a tried-and-tested tool for stage, studio and hi-fi applications. Cable designed to avoid the release of toxic matter in case of fire because they do not contain any halogens. That is why the it is so well-suited for permanent installations in public buildings.


Pictures:



HIGHEST QUALITY - RELIABILITY - INNOVATION

Novacord

Speaker cable 2x1.5, AWG 16, FRNC/LSZH-C, IEC 60332-3-24



- 1 - Jacket
- 2 - Insulation
- 3 - Conductor

Structure

Conductor

Cross Sec. Area	1.5 mm ² , Ø 1.6 mm
No. of Cores	2 cores
Material	OFC
Type of conductor	Stranded
Strands	22/0.3±0.008 mm

Insulation

Material	LSZH-FR
Diameter	2.4 ±0.1 mm
Color	Black, Red

Jacket

Material	FRNC/LSZH-C
Diameter	6.2±0.2 mm
Color	Black, RAL9005

Mechanical properties

Bending radius	without load	25 mm / 4xD (outer diameter)
	with load	50 mm / 8xD (outer diameter)
Max pull tension		200 N
Temperature range		-30°C to +70°C

Electrical properties

at 20 °C

DC Resistance	≤ 11.6 Ω/km
Insulation resistance	> 200 MΩ/km
Operating voltage	50/75V AC/DC
Voltage rating	300V

Speaker cable 2x1.5, AWG 16, FRNC/LSZH-C, IEC 60332-3-24

Standarts

Flame resistance	IEC 60332-3-24
CPR class	Dca
Amt of Halogen	zero

Technical data

Article	Delivery length	Drum size	Weight
500DW	500 m	400/160/200	37.5 kg

© NOVACORD Inc. 2022 All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Novacord Inc. Although Novacord makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission

Novacord Inc. provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Novacord be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Novacord has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Novacord Inc. The information is believed to be correct at the time of issue. Novacord Inc. reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Novacord Inc.

HIGHEST QUALITY - RELIABILITY - INNOVATION

novacord.de