



## ARIAL ExTLiFe SAE 0W-30 BL04

This universal synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEM's and thus has a wide application.

### Performance level:

ACEA C3; API SN/CF; BMW Longlife-04; MB 229.31/229.51/229.52; Renault RN0700/0710

### Product description:

A universal synthetic motor oil, developed according to the most recent technology and based on specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming.

### Packaging:

LITRES	PACKING	PER BOX	PER PALLET
1	Canister	12	*600
5	Canister	4	*120
20	Canister	-	24
60	Barrel	-	9
208	Barrel	-	4
1000	Pallet tank	-	1

\*CP pallet size 114 x 114 cm.

The number of boxes on a pallet may vary depending on the order.

### Typicals:

Density at 15°C, kg/l:	0,847
Viscosity -35°C, mPa.s:	5640
Viscosity 40°C, mm²/s:	59,90
Viscosity 100°C, mm²/s:	12,20
Viscosity Index:	203
Flash Point COC, °C:	224
Pour Point, °C:	-45
Total Base Number, mgKOH/g:	8,0
Sulphate Ash, %:	0,78

### Categories:

Passenger Car

**SKU: AR0030030xx**