



## ARIAL ExTLiFe SAE 0W-20

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars. This oil is fully backward compatible with GM dexos1 Gen 2. This oil is also suitable for the PATAC requirements of China 6 emission norms.

### Performance level:

API SP Resource Conserving; ILSAC GF-6A; GM dexos 1 Gen 3; Chrysler MS 6395; Fiat 9.55535-CR1; Ford WSS-M2C947-A/B1 / WSS-M2C962-A1; GM 6094M

### Product description:

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### Packaging:

LITRES	PACKING	PER BOX	PER PALLET
1	Canister	12	*600
5	Canister	4	*120
20	Canister	-	24
60	Barrel	-	9
208	Barrel	-	4
1000	Pallet tank	-	1

\*CP pallet size 114 x 114 cm.

The number of boxes on a pallet may vary depending on the order.

### Typicals:

Density at 15°C, kg/l:	0,842
Viscosity -35°C, mPa.s:	5740
Viscosity 40°C, mm²/s:	44,50
Viscosity 100°C, mm²/s:	8,40
Viscosity Index:	168
Flash Point COC, °C:	226
Pour Point, °C:	-42
Total Base Number, mgKOH/g:	7,4
Sulphate Ash, %:	0,78

### Categories:

Passenger Car

**SKU: AR0010020xx**