







REV	2	CONTENT	1	CHK	DATE
V0.0		CONTENT		SK	2014-11-29

- NOTES:**
- 1.Rating:300V 8A ,
 - 2.Insulation Withstands Voltage:
AC2000V/MIN
 - 3.Insulation Resistance:
500MΩ or more at DC500V
 - 4.Using Temperature Range:
-40°C--+105°C
 - 5." ★ " is the important dimension



PCB LAYOUT
S=2.5:1



A	Total Pitch Tolerances in mm								Nominal dimension range in mm								$\perp$		$\equiv$		$-$		$//$	
	over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 250	over 250 to 350	over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 200	over 200 to 250	over 250 to 320	over 0 to 10	over 10	all		over 0 to 100	over 100 to 150	over 150
	± 0.18	± 0.20	± 0.25	± 0.3	± 0.35	± 0.4	± 0.60	± 0.70	± 0.85	± 0.20	± 0.25	± 0.30	± 0.35	± 0.44	± 0.55	± 0.70	± 0.80	± 0.90	0.2	0.3	0.3	0.2	0.3	0.5
	6								5								4							

ITEM	NAME OF PART		NO. OF PART		Q"TY	MATERIAL			NOTE		
DWG.	SK	DATE	2014-11-29		SIZE	A4	UNITS	mm	SHEET/OF	1 / 1	
CHK.		DATE			SCALE	4:1		15EDGVM-3.81			
APP.		DATE			NAME						
					DWGNO.						
										1	

