

Push-in terminal blocks-UJ6-6/1 2-421505



Terminal block, Rated current: 1000V, Rated current: 41A, connection methods: circlip connection, number of connection: 2, 0.5mm² - 10mm², AWG : 20-10, thickness 8.2mm, height 42.2mm, color: grey, mounting rail: TH35-7.5、TH35-15.

Product parameter

Parameter	Data
Packing unit(pcs)	40
NW per piece(g)	17
Layers	1
Number of connections	2
Rated cross section(mm ²)	6
Color	grey
Insulation material	PA
Flame retardant grade	V0
Rated voltage(V)	1000
Rated current(A)	41
Temperature of insulation material	-40 ~ +125
Wire feed	Above the terminal

Product certification

Parameter	Data
Certification logo	CE
Certification logo	RoHS

Technical data

Parameter	Data
-----------	------

Parameter	Data
Connection Method	Push in connection
Stripping length(mm)	16
Solid conductors(mm ²)	0.5-10
Solid conductors AWG	20-10
Stranded conductors(mm ²)	0.5-6
Stranded conductors AWG	20-12
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +55
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	77
Thickness(mm)	8.2
Height(mm)	42.2