

XA-TRAN UNI

SYNTHETIC AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

A very high graded automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives.

PROPERTIES

- Important contribution fuel economy.
- Excellent lubrication.
- very good resistance against oxidation and a very high thermal stability.
- excellent resistance against foaming.
- excellent protection against wear.
- very high and stable viscosity index.
- excellent and very stable friction characteristics that enable longer oil-replacement intervals.

APPLICATION

Its versatile nature guarantees it can be used in automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs. Meeting the requirements of most American, Japanese and European manufacturers

TYPICALS

Density at 15 °C	0,849 kg/l
Viscosity -40 °C	12000 mPa.s
Viscosity 40 °C	32,70 mm²/s
Viscosity 100 °C	7,02 mm²/s
Viscosity Index	184
Flash Point COC	218 °C
Pour Point	-48 °C
Color	Red

SPECIFICATIONS

AISIN-WARNER: JWS 3309	AISIN-WARNER: JWS 3314
AISIN-WARNER: JWS 3317	ALLISON : TES 295
BMW: ETL 7045E	BMW: ETL 8072B
BMW: LA 2634	BMW: LT 71141
CHRYSLER: ATF +3 AND +4	FIAT: 9.55550-AV4
FORD: MERCON V	FORD: WSS-M2C922-A1
GM: DEXRON III-H, IIIG & IID	HONDA: ATF Z-1
HYUNDAI: SP-III	MB: 236.10
MB: 236.11	MB: 236.3
MB: 236.5	MB: 236.7
NISSAN: MATIC-K	NISSAN: MATIC-W
PSA: P/N Z 000169756	TOYOTA: TYPE T-IV
VW: G 052 055	VW: G 052 162
VW: G 052 533	VW: G 052 990
VW: G 055 025	

PACKAGING

1L can (12 x 1L carton)
20L drum
60 L drum
208 L drum

