

X-TREME WINTER D

ADVANCED WINTER DIESEL FUEL ADDITIVE

DESCRIPTION

Flow Booster Diesel fuel additive. Improves flow properties of the fuel and increases performance of diesel engines at temperatures up to -30°C.



BASIC BENEFITS

- Allows operation of machines and secures reliability at extreme cold weather.
- Preserves the fluid flow properties of fuel in hard winter storage conditions.
- Economical and easy to use.

PROPERTIES

- Prevents fuel from solidifying at temperatures up to -30°C.
- Eliminates engine damage due to fuel starvation.
- Suitable for all diesel fuels DIN EN 590.
- Contains no alcohols: does not damage diesel fuel injector pumps and seals; does not reduce diesel fuel Cetane number.

APPLICATION

Suitable for all diesel engines, also equipped with Diesel Particle Filters (DPF) grades of diesel fuel for reliable cold operation in severe winter conditions. Suitable for passenger, commercial vehicles, buses and construction machinery.

DIRECTIONS FOR USE

Add 25 ml per 25 litres of diesel fuel (1:1000).

Add before filling up and before diesel fuel starts to freeze.

TYPICALS

Physical state:	liquid	Decomposition temperature:	Undetermined.
Colour:	light yellow	Oxidizing properties:	not oxidizing.
pH-Value:	Not applicable.	Vapour pressure:	Undetermined.
Melting point:	< -45 °C	Density (at 20 °C):	0,85 g/cm ³
Initial boiling point and boiling range:	200 °C	Water solubility (at 20 °C):	Immiscible
Flash point:	65 °C	Partition coefficient:	Undetermined.
Ignition temperature:	236 °C	Viscosity / kinematic:	Undetermined.
Auto-ignition temperature:		Evaporation rate (at 20 °C):	Undetermined.
Solid:	Undetermined.		
Gas:	> 230 °C		

PACKAGING

250 ml can with dosing system (12 x 250 ml carton)
1L can - 60L drum - 200L drum