



Essential Smartbright LED Batten

BN017C LED30/840 2ft

Essential Smartbright LED Batten, 30 W, 3000 lm, 4000 K, Wide beam

Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. This new batten range of LED products can be used to replace traditional battens with fluorescent lamps. The process of selecting, installing and maintaining is so easy – it's a simple switch

Product data

General Information	
Number of gear units	1 unit
Gear	-
Driver included	Yes
Light source engine type	LED
Value ladder	Value
Warranty period	1 years


Light Technical	
Luminous Flux	3,000 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	100 lm/W
Color rendering index (CRI)	80
Number of light sources	1
Beam angle of light source	110 degree(s)
Light source color	840 neutral white

Optic type	Wide beam
Luminaire light beam spread	110°
Unified glare rating CEN	30
Operating and Electrical	
Input Voltage	220 V
Line Frequency	60 Hz
Inrush current	29 A
Inrush time	0.28 ms
Power Consumption	30 W
Power Factor (Fraction)	0.5
Connection	Flying leads/wires
Cable	Cable 0.3 m without plug
Number of products on MCB of 16 A type B	
Number of products on MCB of 16 A type B	17
Suitable for random switching	Not applicable

Essential Smartbright LED Batten

Protection class IEC	Safety class II	CE mark	No
Controls and Dimming		ENEC mark	-
Dimmable	-	Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Control interface	-	Photobiological risk specification	0.2 m
Maximum dim level	Not applicable	EU RoHS compliant	Yes
Mechanical and Housing		Performance ambient temperature Tq	25 °C
Housing Material	Polypropylene	Ambient temperature range	-20 to +40 °C
Reflector material	-		
Optic material	Polypropylene		
Optical cover material	Polypropylene		
Housing Color	White		
Mounting device	Mounting bracket		
Optical cover finish	Opal		
Overall length	560 mm		
Overall width	60 mm		
Overall height	50 mm		
Dimensions (Height x Width x Depth)	50 x 60 x 560 mm		
Ingress protection code	IP20 [No protection]		
Mech. impact protection code	IK03 [0.3 J]		
Optical cover type	Opal		
Net Weight (Piece)	0.240 kg		
Approval and Application			
Glow-wire test	Temperature 650 °C, duration 30 s		
Flammability mark	For mounting on normally flammable surfaces		

Dimensional drawing



Essential Smartbright LED Batten



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com
2025, December 11 – data subject to change