



■ Features :

- Economical open frame design
- Wide input range
- High efficiency up to 97%
- Remote ON / OFF control
- Compact size 2.0"x1.082"x 0.472"(SIP package)
- Protections: Short circuit / Overload / Over voltage
- -30~+85°C wide working temperature
- Cooling by free air convection
- Comply to BS EN/EN55032 ClassA without additional components
- Trimming output (optional)
- 3 years warranty

■ GTIN CODE

MW Search: <https://www.meanwell.com/serviceGTIN.aspx>




SPECIFICATION




ORDER NO.			NID100-5		NID100-12		NID100-15		NID100-24		
OUTPUT	DC VOLTAGE		5V		12V		15V		24V		
	RATED CURRENT		11A		7.5A		6.5A		4.2A		
	RATED POWER		55W		90W		97.5W		100.8W		
	RIPPLE & NOISE (max.) Note.2		100mVp-p		120mVp-p		150mVp-p		200mVp-p		
	LINE REGULATION Note.3		±0.5%		±0.5%		±0.5%		±0.5%		
	LOAD REGULATION Note.4		±0.5%		±0.5%		±0.5%		±0.5%		
	VOLTAGE TOLERANCE		±2.0%		±2.0%		±2.0%		±2.0%		
	SWITCHING FREQUENCY (Typ.)		200KHz								
INPUT	EXTERNAL CAPACITANCE LOAD (max.)		100uf/16V low ESR		68uf/25V low ESR		47uf/50V low ESR		47uf/50V low ESR		
	VOLTAGE RANGE		10.5 ~ 53VDC		20 ~ 53VDC		20 ~ 53VDC		30 ~ 53VDC		
	NORMAL VOLTAGE		24VDC (or 48VDC)		24VDC (or 48VDC)		24VDC (or 48VDC)		48VDC		
	EFFICIENCY (Typ.)	24Vin	93% (12/24VDC)		96%		97%		-----		
		48Vin	92%		95%		95%		96%		
	DC CURRENT	Full load	5400mA/12VDC		4500mA/24VDC		4600mA/24VDC		2300mA/48VDC		
		No load	20mA		30mA		30mA		50mA		
PROTECTION			Fuse recommended (8A)								
PROTECTION	OVERLOAD (Typ.)		120 ~ 300% rated output power								
			Protection type : Hiccup mode, recovers automatically after fault condition is removed								
	OVER VOLTAGE		6.4 ~ 7.5V		15.6 ~ 18V		17.5~ 21V		28~ 33V		
			Protection type : Shut off o/p voltage, clamp by TVS diode								
FUNCTION	REMOTE CONTROL		All output equipped with short circuit								
			Protection type : Hiccup mode, recovers automatically after fault condition is removed								
ENVIRONMENT	SAFETY STANDARDS		EAC TP TC 004 approved								
	WORKING TEMP.		-30 ~ +85℃ (Refer to "Derating Curve")								
	WORKING HUMIDITY		20% ~ 85% RH non-condensing								
	STORAGE TEMP.		-30 ~ +105℃								
	TEMP. COEFFICIENT		±0.03% / ℃ (0 ~ 50℃)								
	VIBRATION		10 ~ 500Hz, 2G 10min./1 cycle, period for 60min. each along X, Y, Z axes								
	SAFETY & EMC	SAFETY STANDARD		BS EN/EN62368-1(LVD)							
EMC EMISSION		Parameter		Standard		Test Level / Note					
		Conducted		BS EN/EN55032		Class A without external components,Class B with external components					
		Radiated		BS EN/EN55032		Class A without external components,Class B with external components					
EMC IMMUNITY		BS EN/EN55035									
		Parameter		Standard		Test Level / Note					
		Radiated		BS EN/EN61000-4-3		Level 2, 3V/m ; criteria A					
		EFT / Burst		BS EN/EN61000-4-4		Level 2, 1KV ; criteria A					
		Surge		BS EN/EN61000-4-5		Level 2, 1KV/Line-Line,criteria A					
		Conducted		BS EN/EN61000-4-6		Level 2, 3V ; criteria A					
		OTHERS	MTBF		17290.5K hrs min. Telcordia SR-332 (Bellcore) ; 1000.6K hrs min. MIL-HDBK-217F (25℃)						
DIMENSION			50.8*27.5*12mm or 2.0**1.082**0.472" inch (L*W*H)								
WEIGHT			35g;280psc/10.8Kg/0.94CUFT								
NOTE	1.All parameters are specified at normal input, rated load, 25℃ 70% RH Ambient. 2.Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor. 3.Line regulation is measured from low line to high line at rated load. 4.Load regulation is measured from 10% to 100% rated load. ※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx										

■ Connection diagram to obtain negative output voltage

Note: input voltage must be $< 30\text{VDC}$.




■ Derating Curve

NID100-5V

NID100-12V,15V

NID100-24V


Mechanical Specification

(Unit:mm[inch], Tolerance:±1[±0.04])




Pin Configuration

Pin No.	Pin_Out
1,2,3,4	+Vout
5,6,7,8	Com
9,10	+Vin
11	N.C.
12	Trim(optional)
13	R.C.

EMC Suggestion Circuit

※Comply to EN55032 Class A without additional componenets ,required external componenets to meet Class B emissssion are as below:



C1/C2	L1	C3
120 μ F/63V	15 μ H(NiZn)	22 μ F/35V