

XA-TRAN 6G

SYNTHETIC AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

A very high graded automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives.

PROPERTIES

- Important contribution fuel economy.
- Excellent lubrication.
- very good resistance against oxidation and a very high thermal stability.
- excellent resistance against foaming.
- excellent protection against wear.
- very high and stable viscosity index.
- excellent and very stable friction characteristics that enable longer oil-replacement intervals.

APPLICATION

This premium synthetic product is specially formulated for the lubrication of ZF 6HP transmissions as fitted in BMW, Jaguar and Land Rover, it is also suitable for other OEMs, who recommend this type of fluid (e.g. Audi Quattro).

TYPICALS

Density at 15 °C	0,845 kg/l
Viscosity -40 °C	9500 mPa.s
Viscosity 40 °C	31,0 mm ² /s
Viscosity 100 °C	6,2 mm ² /s
Viscosity Index	153
Flash Point COC	202 °C
Color	Amber

SPECIFICATIONS

ZF TE-ML 11
AML 4G4319A509/AA/S
BENTLEY PY112995PA
BMW 83220142516, M-1375.4
HYUNDAI 040000C90SG
JAGUAR Fluid 8432
LAND ROVER TYK500050
MASERATI 231603
VW G 055 005

PACKAGING

1L can (12 x 1L carton)
20L drum
60 L drum
208 L drum

