

型号 MODEL NO

SP-601

**类型 Type**



连接方式 Connection type

标准尺寸 Standard Size

符合行业标准 Meet industry standards

Standard(Comply with)**(符合) 标准**ANSI/EIA,RS-310-D,DIN41497;PART
1,DIN41494; PART7,IEC297-2,GB/
T3047.2-92standard**材料 Material:**SPCC high quality cold-rolled steel
SPCC优质冷轧钢**应用 Application:**Installing server interchanger etc.
安装服务器交换机等**产品特点 PRODUCT FEATURE**

- 120毫米风扇, 可选;
- 可拆卸侧面板, 侧锁, 可选;
- 安装方便;
- 去油污、酸洗、磷酸盐防锈、纯水清洗、静电喷涂
- 可调脚和载重脚轮, 可选;
- 焊接框架, 结构可靠;
- 前门转角超过180度;
- 顶盖和底板上开有孔, 用于电缆进入;
- SPCC冷轧钢; 可选厚度: 1.0毫米和1.2毫米
- 120mm fan optional;
- Removable side panels, sides locks optional;
- Easy mounting installation;
- Degreasing, pickling, rust-proof phosphate, pure water cleaning, electrostatic spraying
- Adjustable feet and heavy castors are optional;
- Welded frame, reliable structure;
- Turning angle of front door is over 180 degrees;
- Knock out hole for entering cable on both of top cover and bottom panel;
- SPCC cold rolled steel;Thickness: 1.0mm,1.2mm optional

顶部通风孔
Top ventilation holes小圆锁, 可选
Small round lock is optional可拆卸侧面门, 使用灵活
Removable side door, flexible use顶部通风孔
Fan ventilation holes**SP机柜说明 SP Cabinets Specification**

型号 Model	容量 (U) Capacity (U)	宽 (毫米) Width(mm)	深 (毫米) Depth(mm)	高度 (毫米) Height(mm)	组装体积(立方米) Assemble volume(CBM)
SP-601-6404	4	600	450	252	0.068
SP-601-6406	6			352	0.095
SP-601-6409	9			502	0.136
SP-601-6412	12			642	0.173
SP-601-6415	15			782	0.211
SP-601-6604	4	600	600	252	0.091
SP-601-6606	6			352	0.127
SP-601-6609	9			502	0.181
SP-601-6612	12			642	0.231
SP-601-6615	15			782	0.282