

Product Information Guide



PVC Floor Marking Tapes - Conformable

Application(s):

Our general purpose PVC Floor Marking Tapes are a great choice for floor aisle marking and colour-coding pipe banding applications. The colouring is throughout the vinyl so it can not scratch or scuff during wear. The PVC film is formulated with a crosslinked rubber adhesive providing good adhesive tack and flow, making it a good choice for most industrial applications.

General Properties:

Adhesive Type	Crosslinked Rubber Adhesive
Carrier	Vinyl
Colours	Orange, Blue, Red, White, Yellow, Black, Green, Black/Yellow, Red/White
Total Thickness	0.15 mm
Liner	No Liner - Tapes are Self Wound
Operational Temperature	-20°C to +60°C
Minimum Application Temperature	+10°C
Storage Conditions	+15°C to +30°C / <50% R.H.
Shelf Life	1 Year

PVC Film:

Web Type	PVC Film
Thickness	0.1324 mm
Tensile Strength	6.8 kg/25 mm
Elongation	>150%

Rubber Adhesive:

Dry Coat Weight	35 g/m ²
180 Peel Adhesion	>0.45 kg/25 mm

Oil, Chemical and UV Resistance:

Engine Oil	Good
Gear Oil	Good
Hydraulic Oil	Good
Fuel	Good
Liquid Anti-Freeze	Good
Water	Good
Liquid Soap	Good
Sulphuric Acid	Good
Alcohol	Good
UV	Good

Recommended Utilities:

Floor Tape Applicator	Good
-----------------------	------