

PRO-LL 0w20

HIGH PERFORMANCE FULL SYNTHETIC ENGINE OIL

DESCRIPTION

Synthetic high performance engine oil produced with special selected base oils with a high viscosity index and a well balanced choice of advanced additives. Provides optimum protection and extended engine life and reliability. Combines exceptional anti-wear performance and outstanding high temperature protection with excellent cold start characteristics. This motor oil also contributes to the extension of the lifetime of particle filters.

PROPERTIES

- Fuel economy.
- High and very stable viscosity index.
- Very fast cold start.
- Safe lubrication film at extreme temperatures.
- Flexible and extended oil drain intervals.
- High protection against wear.
- Mid SAPS / DPF- compatible.
- Dark Green.

APPLICATION

Suitable for both turbocharged and normally aspirated engines to ensure maximum economy and reduced emissions (CO₂). MID SAPS technology. Specially designed to optimum performance in today's VW-Group engines where VW 508.00/509.00 specifications are required. Apply the correct amount of oil indicated in the operating instructions of the vehicle and engine manufacture.

TYPICALS

Density at 15 °C	0,832 kg/l
Viscosity -35 °C	3330 mPa.s
Viscosity 40 °C	39,30 mm ² /s
Viscosity 100 °C	7,93 mm ² /s
Viscosity Index	179
Flash Point COC	220 °C
Pour Point	-57 °C
Total Base Number	8,3 mgKOH/g
Sulphate Ash	0,78 %

SPECIFICATIONS

VW 508.00/509.00

PACKAGING

1L can (12 x 1L box)
5L can (4 x 5L box)
60 L drum
208 L drum

