

ART. P320 - ART. P321

CODE	SIZE	FEATURES	MODEL	
88P3200153	1"1/2	25/40	Grundfos	
88P3210153	1"1/2	25/65	Grundfos	

Asynchronous circulator for closed loop heating systems, interaxe distance 130 mm. NOT FOR SALE IN THE EU



ART. P328

CODE	SIZE	FEATURES	
88P3280153	1"1/2	25/70	

Grundfos UPM3 HYBRID 25-70 electronic circulator, interaxe distance 130 mm. Variable pressure, constant pressure, contant curves, AUTO ADAPT, PWM signal. POWER SUPPLY CABLE INCLUDED. The pump can be controlled via PWM signal. PWM signal cable **NOT INCLUDED.**



ART. P326

CODE	SIZE	FEATURES	
88P3260153	1"1/2	25/70	

Electronic circulator Grundfos UMP3 PWM 25-70, interaxe distance 130 mm. With PWM signal. POWER SUPPLY CABLE INCLUDED. PWM signal cable **NOT INCLUDED.**



ART. P330

CODE	SIZE	FEATURES	
88P3300153	1"1/2	25/7	

Electronic circulator WILO PARA RS 25/7, interaxis distance 130 mm. Variable pressure, constant pressure, constant curves. Power supply cable included.



ART. P327

CODE	SIZE	FEATURES	
88P3270153	1"1/2	25/8	

Electronic circulator WILO PARA RS 25/8, interaxe distance 130 mm. Variable pressure, constant pressure, contant curves. Power supply cable included.



ART. S160

CODE	SIZE	FEATURES	
88S1600199G	1"	15/60	
88S1600199	1"	20/60	

Asynchronous circulation pump for solar systems, interaxe distance 130 mm. NOT FOR SALE IN THE EU.