LL1116 | Ball valve,female/female, flat lever handle



CE ACS

Features	
Working pressure	16 bar (232 psi)
Working temperature	from –10°C to +120°C (from 14 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Opening/closing test	10000 times

Size	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"

LL1118 | Ball valve,female/female, T handle




CE ACS

Features	
Working pressure	16 bar (232 psi)
Working temperature	from –10°C to +120°C (from 14 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Opening/closing test	10000 times

Size	1/2"	3/4"	1"	1"1/4

DOUBLE-LIN VALVES

LL1117 | Ball valve, male/female, flat lever handle




CE ACS

Features	
Working pressure	16 bar (232 psi)
Working temperature	from –10°C to +120°C (from 14 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Opening/closing test	10000 times

Size	1/2"	3/4"	1"

LL1119 | Ball valve, male/female, T handle



CE ACS

Features	
Working pressure	16 bar (232 psi)
Working temperature	from –10°C to +120°C (from 14 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Opening/closing test	10000 times

Size	1/2"	3/4"	1"	1"1/4

DOUBLE-LIN VALVES

LL1004 | Ball valve, full flow, male/male, flat lever handle



ACS EAC

Features	
Working pressure	25 bar (362.5 psi)
Working temperature	from –10°C to +120°C (from 14 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Opening/closing test	10000 times

Size	1/4"	3/8"	1/2"	3/4"	1"

LL1036 | Ball valve, full flow, male/male, T handle



ACS EAC

Features	
Working pressure	25 bar (362.5 psi)
Working temperature	from –10°C to +120°C (from 14 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Opening/closing test	10000 times

Size	1/4"	3/8"	1/2"	3/4"	1"

LL1038 | Ball valve, full flow, female/female, lever handle



CE ACS EAC

Features	
Working pressure	25 bar (362.5 psi)
Working temperature	from –10°C to +120°C (from 14 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Opening/closing test	10000 times

Size	1/4"	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"

LL1060 | Ball valve, full flow, female/female, aluminium handle




CE ACS EAC

Features	
Working pressure	25 bar (362.5 psi)
Working temperature	from –10°C to +120°C (from 14 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Opening/closing test	10000 times

Size	1/2"	3/4"	1"	1"1/4	1"1/2	2"

DOUBLE-LIN VALVES

LL1039 | Ball valve, full flow, male/female, lever handle




CE ACS EAC

Features	
Working pressure	25 bar (362.5 psi)
Working temperature	from –10°C to +120°C (from 14 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Opening/closing test	10000 times

Size	1/4"	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"

LL1061 | Ball valve, full flow, male/female, aluminium handle



CE ACS EAC

Features	
Working pressure	25 bar (362.5 psi)
Working temperature	from –10°C to +120°C (from 14 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Opening/closing test	10000 times

Size	1/2"	3/4"	1"	1"1/4	1"1/2	2"

DOUBLE-LIN VALVES

LL1140 | Brass ball valve with probe connection, flat lever handle



CE

Features	
Working pressure	16 bar (232 psi)
Working temperature	from –10°C to +120°C (from 14 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Opening/closing test	10000 times

Size	1/2"	3/4"	1"	1"1/4	1"1/2

LL1141 | Brass ball valve with probe connection, T handle



CE

Features	
Working pressure	16 bar (232 psi)
Working temperature	from –10°C to +120°C (from 14 °F to 248 °F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Opening/closing test	10000 times

Size	1/2"	3/4"	1"