LL8042 | Stainless steel corrugated hose

Features

Working pressure	16 bar (232 psi)
Working temperature	Lower than 90℃ (Lower than 194 ˚F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Working medium	water,noncorrosive liquid,saturated steam,air



EAC

SIZE:
F1/2"xF1/2"

DOUBLE-LIN VALVES

LL8043 | Stainless steel corrugated hose

Features

Working pressure	16 bar (232 psi)
Working temperature	Lower than 90℃ (Lower than 194 ˚F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Working medium	water,noncorrosive liquid,saturated steam,air



EAC

SIZE:
F1/2"xM1/2"

DOUBLE-LIN VALVES

LL8219 | Stainless steel corrugated hose

Features

Working pressure	16 bar (232 psi)
Working temperature	Lower than 90℃ (Lower than 194 ˚F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Working medium	water,noncorrosive liquid,saturated steam,air



EAC

SIZE:
F1/2"xF1/2" F3/4"xF3/4"

LL8220 | Stainless steel corrugated hose


Features

Working pressure	16 bar (232 psi)
Working temperature	Lower than 90℃ (Lower than 194 ˚F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Working medium	water,noncorrosive liquid,saturated steam,air



EAC

SIZE:
F1/2"xM1/2" F3/4"xM3/4"



DOUBLE-LIN VALVES

LL8087 | Stainless steel corrugated hose

Features

Working pressure	16 bar (232 psi)
Working temperature	Lower than 90℃ (Lower than 194 ˚F)
Thread	ISO228 (equivalent to DIN 259 and BS2779)
Working medium	water,noncorrosive liquid,saturated steam,air



SIZE:
M1/2"xM1/2" M3/4"xM3/4"

DOUBLE-LIN VALVES

LL1284 | Teflon tape

Features

Density available	0.25g/m³ 0.30g/m³



0.25g/cm³	
12mm × 0.075mm × 10m	19mm × 0.075mm × 10m
12mm × 0.1mm × 10m	19mm × 0.1mm × 10m
0.30g/cm³	
12mm × 0.075mm × 10m	19mm × 0.075mm × 10m
12mm × 0.1mm × 10m	19mm × 0.1mm × 10m